




Europäisches
Patentamt

European
Patent Office

Office européen
des brevets

PCT/IB04/52066



Bescheinigung

Certificate

Attestation

Die angehefteten Unterla-
gen stimmen mit der
ursprünglich eingereichten
Fassung der auf dem näch-
sten Blatt bezeichneten
europäischen Patentanmel-
dung überein.

The attached documents
are exact copies of the
European patent application
described on the following
page, as originally filed.

Les documents fixés à
cette attestation sont
conformes à la version
initialement déposée de
la demande de brevet
européen spécifiée à la
page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

03103945.6



Der Präsident des Europäischen Patentamts;
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets
p.o.

R C van Dijk

BEST AVAILABLE COPY



Anmeldung Nr:
Application no.: 03103945.6
Demande no:

Anmeldetag:
Date of filing: 24.10.03
Date de dépôt:

Anmelder/Applicant(s)/Demandeur(s):

Koninklijke Philips Electronics N.V.
Groenewoudseweg 1
5621 BA Eindhoven
PAYS-BAS

Bezeichnung der Erfindung/Title of the invention/Titre de l'invention:
(Falls die Bezeichnung der Erfindung nicht angegeben ist, siehe Beschreibung.
If no title is shown please refer to the description.
Si aucun titre n'est indiqué se référer à la description.)

Method and apparatus for providing a video signal

In Anspruch genommene Priorität(en) / Priority(ies) claimed / Priorité(s)
revendiquée(s)
Staat/Tag/Aktenzeichen/State/Date/File no./Pays/Date/Numéro de dépôt:

Internationale Patentklassifikation/International Patent Classification/
Classification internationale des brevets:

G11B27/00

Am Anmeldetag benannte Vertragsstaaten/Contracting states designated at date of
filing/Etats contractants désignées lors du dépôt:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LU MC NL
PT RO SE SI SK TR LI

Method and apparatus for providing a video signal

The invention relates to a method of providing a video signal for display of a stream of video data at a rate other than real-time, the video data being built up from frames, the method comprising the step of real-time rendering of non-contiguous segments of the stream of video data comprising multiple subsequent frames to a first rendered stream.

- 5 The invention further relates to an apparatus for providing a video signal for display of a stream of video data at a rate other than real-time, the video data being built up from frames, the method comprising a first rendering unit for real-time rendering of non-contiguous segments of the stream of video data comprising multiple subsequent frames to a first rendered stream.

- 10 The invention also relates to a record carrier comprising computer executable code.

Furthermore, the invention relates to a programmed computer.

- 15 An embodiment of the aforementioned method is known from the granted US patent US-B-5457669. This document discloses a program search method including the steps of reproducing the program for a predetermined reproduction period after performing a jump step by a predetermined search interval and repeatedly performing the jumping and reproducing steps.

- 20 A disadvantage of such a method is that a user easily loses track of the location at which the program is reproduced. Especially in case of frequent scene changes and/or a large search interval this is the case. First, a user will easily lose any understanding of the search direction. Second, the user might miss some scenes, especially in case of frequent scene changes and a large search interval and in that way, lose the global
25 understanding of the program.

It is an objective of the invention to provide better user feedback using the aforementioned method.

This object is achieved with the method according to the invention, characterised in that the method further comprises the step of: non real-time rendering of the stream of video data by rendering pre-determined non subsequent frames at a speed other than real-time to a second rendered stream; multiplexing the first rendered stream and the second rendered stream for simultaneous display on a display device, wherein: the first rendered stream is displayed on a first part of the display device; and the second rendered stream is displayed on a second part of the display device.

By non real-time rendering of the stream of video data by rendering pre-determined non subsequent frames at a speed other than real-time, a stream is obtained as is usually obtained when for example fast forwarding a film on a standard DVD player. In such a stream, the direction of the playback can easily be seen, for example when a person is shown who is walking backward instead of forward, especially at playback speeds which are not too high. This type of play-back, however, has the disadvantage that it is very difficult to render synchronously with audio, while play-back with audio increases the information delivered to a user. Therefore, rendering of two streams is provided in the method according to the invention.

In an embodiment of the method according to the invention, the second part of the display device is significantly smaller than the full size of the display device and the first part of the display is the complement to the second part.

An advantage of this embodiment is that the real-time rendered part of the stream, which is usually the most convenient to view for a user, of data is provided on a large area. The second rendered stream is provided only for navigation and orientation purposes to provide a global impression; therefore it is not a big problem to provide this on a small part of the display device.

A further embodiment of the method according to the invention comprises the steps of providing a first bar representative of the stream of video data and indicating on the first bar a location of the first rendered stream that is displayed on the first part of the display device.

An advantage of this embodiment is that a user is given an indication which part of the stream of audiovisual data is rendered and shown on a screen.

Alternatively, an embodiment according to the invention further comprises the steps of providing a second bar representative of the stream of video data and indicating on the second bar a location of the second rendered stream that is displayed on the second part of the display device.

Another embodiment of the method according to the invention comprises the step of providing an indicator indicative of the direction of the non real-time rendering.

The apparatus according to the invention is characterised in that the apparatus further comprises a second rendering unit for non real-time rendering of the stream of video data by rendering pre-determined non subsequent frames at a speed other than real-time to a second rendered stream; and a multiplexer for multiplexing the first rendered stream and the second rendered stream for simultaneous display on a display device, wherein the first rendered stream is displayed on a first part of the display device; and the second rendered stream is displayed on a second part of the display device.

With respect to the record carrier according to the invention, the computer executable code enables a processing unit to perform the method according to claim 1.

The programmed computer according to the invention is enabled to execute the method according to claim 1.

The invention will now be further elucidated by describing embodiments depicted in Figs., wherein:

Fig. 1 shows a consumer electronics system comprising an embodiment of the apparatus according to the invention;

Fig. 2 shows a stream of audiovisual data to elucidate an embodiment of the method according to the invention;

Fig. 3A shows a screen to depict an embodiment of the method according to the invention;

Fig. 3B shows a screen to depict another embodiment of the method according to the invention;

Fig. 4A shows a screen to depict a further embodiment of the method according to the invention;

Fig. 4 B shows a screen to depict yet another embodiment of the method according to the invention; and

Fig. 5 shows a screen to depict yet a further embodiment of the method according to the invention.

Fig. 1 shows a consumer electronics system 100 comprising a video processing apparatus 110 as an embodiment of the apparatus according to the invention, a TV-set 150 and a user control device 160.

The video processing apparatus 110 comprises a harddisk drive 112 as an embodiment of a storage device, a buffer 114, a first rendering unit 116, a second rendering unit 118, a video multiplexing unit 120, a micro controller 122 for controlling the components of the video storage apparatus 110, a ROM memory 124 and a user control command receiver 126.

The TV-set 150 comprises two speakers 152 and a screen 154 as a display device.

The user control device 160 comprises a fast rewind button 162, a real-time play button 164, a fast forward button 166, a pause button 168 and a stop button 170.

When performing fast trickplay – fast forward or fast backward – while displaying video data on the screen 154 according to the invention, data is retrieved from the harddisk drive 112 and stored in the buffer 114. It should be mentioned that the buffer 114 is optional; data can also be read directly from the harddisk drive 112. A buffer is, however, preferred since in that case, data has to be read only once from the harddisk drive 112, as will be apparent from the further description.

Using the method according to the invention, at least two rendered streams are produced. A first rendered stream is produced by real-time rendering of non-contiguous segments of the stream of video data comprising multiple subsequent frames by the first rendering unit 116. Also, a second stream is produced by non real-time rendering of the stream of video data by rendering pre-determined non subsequent frames at a speed other than real-time by the second rendering unit 118, for example at a higher speed.

To execute the method according to the invention, the rendering units are controlled by the micro controller 122 for controlling the components of the video storage apparatus 110. The instructions for the micro controller 122 for executing the method according to the invention are in this embodiment stored in the ROM memory 124 as an embodiment of the data carrier according to the invention.

The operation of the video processing apparatus 110 and embodiments of the method according to the invention will be elucidated by Fig. 1 and by Fig. 2 depicting a stream of video data 200. The stream of video data 200 is built up from frames.

When a user instructs the video processing apparatus 110 to render a stream of video data 200 at a speed higher than real-time in fast forward mode, the user pushes the fast

forward button 164 on the user control device 160. The user command is received by the user control command receiver 126, which forwards it to the micro controller 122. The micro controller 122 instructs the buffer 114 to retrieve a first portion of the stream 200 between the most left arrow of a first indicator 202 and the most left arrow of a second indicator 204 from the harddisk drive 112 and buffer it.

Next, a part of the first portion of the stream 200 between the most left arrow and most right arrow of the first indicator 202 is retrieved from the buffer 114 and is rendered by the first rendering unit 116 to form a first rendered stream by real-time rendering of the first portion of the stream 200. In this embodiment, the first rendered stream has a pre-determined duration.

Simultaneously, pre-determined non subsequent frames of the first portion of the stream 200 are retrieved from the buffer 114 and rendered by the second rendering unit 118 to provide a second rendered stream with the same pre-determined duration of the first rendered stream. The pre-determined frames are for example intra-coded frames when the stream 200 is encoded according to the MPEG (Motion Pictures Expert Group) standard. In Fig. 2, they are for the first portion indicated by a first arrow 212, a second arrow 214, a third arrow 216 and a fourth arrow 216.

The second and the first stream are rendered simultaneously. This means that as the first frame of the segment indicated by the first indicator 202 is rendered to the rendered first stream, the frame indicated by the first arrow 212 is rendered to the second rendered stream. Furthermore, as the segment indicated by the first indicator 202 is rendered, the frames indicated by the second arrow 214, the third arrow 216 the fourth arrow 216 and a fifth arrow 218 are rendered to the second rendered stream. Subsequently, the first frame of the segment indicated by the second indicator 204 is rendered simultaneously with the frame indicated by a sixth arrow 220. In this way, the stream 200 is rendered at a speed faster than real-time.

This is the point where the advantage of the buffer 114 comes in. When the first portion of the stream 200 is retrieved directly from the harddisk drive 112 by both rendering units individually, the harddisk drive 112 is busy for a longer time, since during rendering to obtain the second rendered stream multiple frames continuously have to be retrieved. When they are retrieved at once, the harddisk drive 112 is available for further processes.

Advantageously, only the part of the first portion of the stream 200 between the most left arrow and most right arrow of the first indicator 202 and the frames indicated by

the first arrow 212, the second arrow 214, the third arrow 216 and the fourth arrow 216 are buffered.

When the first portion of the stream 200 between the most left arrow and most right arrow of the first indicator 202 and the pre-determined frames of the first portion are rendered, a second portion of the stream 200 between a fifth arrow 220 and a sixth arrow 228 is retrieved from the harddisk drive 112 and stored in the buffer 114 for further rendering.

Both rendered streams are sent to the video multiplexing unit 120, where they are multiplexed to be displayed simultaneously on the screen 154, wherein each rendered stream is displayed in a pre-determined part of the screen 154.

Advantageously, sound is rendered and provided to the TV-set as well, accompanying the first rendered stream. The sound is provided to a user via the two speakers 152. The sound is provided at the speed of the first stream, which is preferably real-time.

As the first stream comprises non-contiguous segments, rendered in real-time and the second stream comprises

It will be apparent to a person skilled in the art that additional features are needed for properly providing a signal to the TV-set 150, like a D/A converter. However, since they are apparent, they have been omitted in Fig. 1 for sake of simplicity and overview.

When the stream 200 is compressed and/ or encrypted, the multiplexing may take place either in the compressed and/ or encrypted domain or in the non-compressed and/ or decrypted domain. In the first case, the rendering units are replaced by simple processing units retrieving the proper frames from the buffer 114 and the actual rendering is done after multiplexing. In this case, an additional rendering unit (not shown) has to be inserted in the video processing apparatus 110.

In the latter case, the decryption and/ or decompression is performed by the rendering units or by separate decryption and/ or decompression units that are placed between the harddisk drive 112 and the rendering units. There are several embodiments for this; in one embodiment, one rendering unit (not shown) is placed between the harddisk drive 112 and the buffer 114. In a further embodiment, a first decryption (or decompression) unit is placed between the buffer 114 and the first rendering unit 116 and a second first decryption (or decompression) unit is placed between the buffer 114 and the second rendering unit 116. This kind of additions to and permutations of the elements of the embodiment described are obvious by a person skilled in the art and can be performed without departing from the scope of the invention.

When the stream of video data 200 is displayed using the method according to the invention, wherein each rendered stream is displayed on a pre-determined part of the display device 154, various embodiments are possible, some of which are presented by Fig. 3A and Fig. 3B.

5 Fig. 3A shows the TV-set 150 with the screen 154 on which a first part 310 and a second part 320 are indicated, both parts occupying half the area of the screen to elucidated an embodiment of the method according to the invention. A first rendered stream obtained by real-time rendering of non-contiguous segments of a stream of video data comprising multiple subsequent frames is displayed on the first part 310 and a second
10 rendered stream obtained by non real-time rendering of the stream of video data by rendering pre-determined non subsequent frames at a speed higher than real-time is displayed on the second part 320.

 Fig. 3B shows the TV-set 150 with the screen 154 on which a first part 340 and a second part 350 are indicated to elucidate a further embodiment of the method
15 according to the invention, wherein the second part 350 is substantially smaller than the first part 340. A first rendered stream obtained as described in the previous paragraph is displayed on the first part 340 and a second rendered stream obtained as described in the previous paragraph is displayed on the second part 350.

 It will be apparent for a person skilled in the art that a further embodiment of
20 the invention is possible, wherein the first rendered stream is displayed on the second part 350 and the second rendered stream is displayed on the first part 340. In another embodiment, a user may even switch between both modes described here, swap the displayed streams in the first part 340 and the second part 350.

 To further enhance navigation of a user through a stream of video data during
25 trickplay wherein the stream is displayed using an embodiment of the method according to the invention, navigation bars are introduced according to an embodiment of the invention. This is elucidated by Fig. 4A and Fig. 4B.

 Fig. 4A shows the TV-set 150 with the screen 154 on which a first part 410 and a second part 420 are indicated. A first rendered stream obtained as described above is
30 displayed on the first part 410 and a second rendered stream obtained as described above is displayed on the second part 420. Furthermore, a first bar 412 with a first indicator 414 and a second bar 422 with a second indicator 424 are displayed on the screen 154.

 Both bars represent at least a portion of a stream of video data that is displayed on the screen 154. The first bar 412 is displayed on the first part 410 of the screen 154 and

the first indicator 414 indicates the location at which the stream of video data is displayed on the first part 410. The second bar 422 is displayed on the second part 420 of the screen 154 and the second indicator 424 indicates the location at which the stream of video data is displayed on the second part 420.

5 Fig. 4B shows the TV-set 150 with the screen 154 on which a first part 440 and a second part 450 are indicated. A first rendered stream obtained as described above is displayed on the first part 440 and a second rendered stream obtained as described above is displayed on the second part 450. Furthermore, a bar 462 with a first indicator 464 and a second indicator 466 are displayed on the screen 154.

10 The bar 462 represents at least a portion of a stream of video data that is displayed on the screen 154. The first indicator 464 indicates the location at which the stream of video data is displayed on the first part 440. The second indicator 466 indicates the location at which the stream of video data is displayed on the second part 450.

15 In a further embodiment borders with different colours are placed around the first part 440 and the second part 450. A colour surrounding the first part corresponds with the first indicator 464 and a colour surrounding the second part corresponds with the second indicator 466.

20 When non-contiguous segments of a stream of video data to be displayed in real-time using the method according to the invention, it might be difficult for a user to keep track of the direction in which the video data is rendered, i.e. backward or forward. To facilitate the user feedback, in an embodiment of the invention, an indicator is provided that indicates the direction of the rendering. This indicator for example has the shape of an arrow, pointing either to the left side (backward rendering) or to the right side (forward rendering).

25 This is indicated in Fig. 5, depicting the TV-set 150 with the screen 154, a first region 510, a second region 520 and an indicator 530 indicating that the rendering direction of the video is forward.

30 It will be apparent to any person skilled in the art that numerous variations based on the embodiments described are possible without departing from the scope of the invention. Process steps performed by multiple elements can be grouped and performed by only one processing element and on the other hand, processing steps performing multiple steps in the embodiments may just as well be taken apart and performed by multiple processing blocks. This also means that all process steps can be performed by a single processor of a programmed computer.

In summary, The invention relates to a method of providing a video signal for display of a stream of video data at a rate other than real-time, the video data being built up from frames, the method comprising the step of real-time rendering of non-contiguous segments of the stream of video data comprising multiple subsequent frames to a first rendered stream; wherein the method further comprises the step of non real-time rendering of the stream of video data by rendering pre-determined non subsequent frames at a speed other than real-time to a second rendered stream; multiplexing the first rendered stream and the second rendered stream for simultaneous display on a display device, wherein: the first rendered stream is displayed on a first part of the display device; and the second rendered stream is displayed on a second part of the display device.

CLAIMS:

1. Method of providing a video signal for display of a stream (200) of video data at a rate other than real-time, the video data being built up from frames (212), the method comprising the step of real-time rendering of non-contiguous segments (202) of the stream of video data comprising multiple subsequent frames to a first rendered stream;

5 characterised in that the method further comprises the step of:

(a) non real-time rendering of the stream of video data by rendering pre-determined non subsequent frames at a speed other than real-time to a second rendered stream;

(b) multiplexing the first rendered stream and the second rendered stream for simultaneous display on a display device (150), wherein:

10 i) the first rendered stream is displayed on a first part (310) of the display device; and

ii) the second rendered stream is displayed on a second part (320) of the display device.

15 2. Method according to claim 1, wherein the second part of the display device is significantly smaller than the full size of the display device and the first part of the display is the complement to the second part.

3. Method according to claim 1, wherein the first part of the display device is significantly smaller than the full size of the display device and the second part of the display is the complement to the second part.

4. Method according to claim 1, wherein the first part of the display device and the second part of the display device have mutually equal sizes.

25

5. Method according to claim 1, wherein the method further comprises the steps of:

(a) providing a first bar (412) representative of the stream of video data;

(b) indicating on the first bar the location of the first rendered stream that is displayed on the first part of the display device.

6. Method according to claim 1, wherein the method further comprises the steps

5 of

(a) providing a second bar (422) representative of the stream of video data;

(b) indicating on the second bar a location of the second rendered stream that is displayed on the second part of the display device.

10 7. Method according to claim 1, wherein the method further comprises the steps of claim 5 and claim 6.

8. Method according to claim 5, wherein the method further comprises the step of indicating on the first bar a location of the second rendered stream that is displayed on the
15 second part of the display device.

9. Method according to claim 1, wherein the method further comprises the step of providing an indicator indicative of the direction of the non real-time rendering.

20 10. Method according to claim 1, further comprising the step of providing an audio signal at real-time, synchronised with the first rendered stream.

11. Apparatus (110) for providing a video signal for display of a stream (200) of video data at a rate other than real-time, the video data being built up from frames (212), the
25 method comprising a first rendering unit (116) for real-time rendering of non-contiguous segments (202) of the stream of video data comprising multiple subsequent frames to a first rendered stream;

characterised in that the apparatus further comprises:

30 (a) a second rendering unit (118) for non real-time rendering of the stream of video data by rendering pre-determined non subsequent frames at a speed other than real-time to a second rendered stream; and

(b) a multiplexer (120) for multiplexing the first rendered stream and the second rendered stream for simultaneous display on a display device (150), wherein:

- i) the first rendered stream is displayed on a first part (310) of the display device;
and
- ii) the second rendered stream is displayed on a second part (320) of the display device.

5

12. Record carrier (124) comprising computer executable code, wherein the computer executable code enables a processing unit to perform the method according to claim 1.

10

13. Programmed computer programmed to execute the method according to claim 1.

ABSTRACT:

The invention relates to a method of providing a video signal for display of a stream of video data (200) at a rate other than real-time, the video data being built up from frames, the method comprising the step of real-time rendering of non-contiguous segments of the stream of video data comprising multiple subsequent frames to a first rendered stream; wherein the method further comprises the step of non real-time rendering of the stream of video data by rendering pre-determined non subsequent frames at a speed other than real-time to a second rendered stream; multiplexing the first rendered stream and the second rendered stream for simultaneous display on a display device (150), wherein: the first rendered stream is displayed on a first part (310) of the display device; and the second rendered stream is displayed on a second part (320) of the display device.

Fig. 1




FIG.1




FIG.2




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B




FIG. 5